

Red. broj	OPRUGA		DIMENZIJE					SILA ZA UGIB		PRIMEDBA
	OZNAKA	TIP	Ds	Du	s	h	Lo	\approx 075h	N(Newton)	
15	TO 50	A	50	25.4	3	1.1	4.1	0.83	12000	
		B	50	25.4	2	1.4	3.4	1.05	4760	
		C	50	25.4	1.25	1.6	2.85	1.2	1550	
16	TO 56	A	56	28.5	3	1.3	4.3	0.98	11400	
		B	56	28.5	2	1.6	3.6	1.2	4440	
		C	56	28.5	1.5	1.95	3.45	1.46	2620	
17	TO 63	A	63	31	3.5	1.4	4.9	1.05	15000	
		B	63	31	2.5	1.75	4.25	1.31	7190	
		C	63	31	1.8	2.35	4.15	1.76	4240	
18	TO 71	A	71	36	4(3.75)	1.6	5.6	1.2	20500	
		B	71	36	2.5	2	4.5	1.5	6730	
		C	71	36	2	2.6	4.6	1.95	5140	
19	TO 80	A	80	41	5(4.7)	1.7	6.7	1.28	33600	
		B	80	41	3	2.3	5.3	1.73	10500	
		C	80	41	2.25	2.95	5.2	2.21	6610	
20	TO 90	A	90	46	5(4.7)	2	7	1.5	31400	
		B	90	46	3.5	2.5	6	1.88	14200	
		C	90	46	2.5	3.2	5.7	2.4	7680	
21	TO 100	A	100	51	6(5.6)	2.2	8.2	1.65	48000	
		B	100	51	3.5	2.8	6.3	2.1	13100	
		C	100	51	2.7	3.5	6.2	2.63	8610	
22	TO 112	A	112	57	6(5.6)	2.5	8.5	1.88	43700	
		B	112	57	4(3.5)	3.2	7.2	2.4	17800	
		C	112	57	3	3.9	6.9	2.93	10500	
23	TO 125	A	125	64	8(7.5)	2.6	10.6	1.95	85900	
		B	125	64	5(4.7)	3.5	8.5	2.63	29900	
		C	125	64	3.5	4.5	8	3.38	15400	
24	TO 140	A	140	72	8(7.5)	3.2	11.2	2.4	85200	
		B	140	72	5(4.7)	4	9	3	27900	
		C	140	72	3.8	4.9	8.7	3.68	17200	
25	TO 160	A	160	82	10(9.4)	3.5	13.5	2.63	138000	
		B	160	82	6(5.6)	4.5	10.5	3.38	41000	
		C	160	82	4.3(4.15)	5.6	9.9	4.2	21800	
26	TO 180	A	180	92	10(9.4)	4	14	3	125000	
		B	180	92	6(5.6)	5.1	11.1	3.83	37500	
		C	180	92	4.8(4.6)	6.2	11	4.65	26400	
27	TO 200	A	200	102	12(11.25)	4.2	16.2	3.15	183000	
		B	200	102	8(7.5)	5.6	13.6	4.2	76400	
		C	200	102	5.5(5.3)	7	12.5	5.25	36100	
28	TO 225	A	225	112	12(11.25)	5	17	3.75	171000	
		B	225	112	8(7.5)	6.5	14.5	4.88	70700	
		C	225	112	6.5(6.2)	7.1	13.6	5.33	44600	
29	TO 250	A	250	127	14(13.1)	5.6	19.6	4.2	249000	
		B	250	127	10(9.4)	7	17	5.25	119000	
		C	250	127	7(6.7)	7.8	14.8	5.85	50500	

Osim navedenih nudimo vam tanjiraste opruge van normi DIN 2093 kao i razne vrste lisnatih opruga prema vašem zahtevu.